



To remove connector from panel insert release key in slot above connector.
Slide out connector.
To install simply push connector into panel until spring locks.



No. 1237 Miniature Strippanels are molded panels designed to mount No. 1210 miniature Jacks. Connectors are installed from the rear and snap in place with spring clips. They are easily removed by releasing spring clip with a release key. No loose connector mounting hardware. Circuit identification is distinct as each circuit is numbered, lettered and color coded. Self-contained hardware provides front mounting in panels to 1/4" thick. Strippanel is molded of color coded thermoset compound that withstands ambient temperatures to 400°F (205°C) continuous and 500°F (260°C) intermittent. High temperature panels that will withstand ambient temperatures to 800°F (425°C) continuous and 1000°F (540°C) intermittent are molded of a red thermoset compound.

For corrosive application, gold plated contacts are available. Caution — system errors can result from use of plated contacts if significant thermal gradients exist at connection.

Available in modules from 2 circuits to 8 circuits. Standard strippanels are provided with Mini Jacks for horizontal mounting, as shown.

TO ORDER:

1. Give Strippanel No. 1237 - 6 - J
2. Specify Number of circuits 6
3. Specify Thermocouple Type J
4. For Hi-Temp Strippanel: 1337 - 6 - J
5. For vertical rows add suffix "V"
e.g. 1237 - 6 - J - V

NUMBER OF CIRCUITS	"A" DIMENSION PANEL OAL		"B" DIMENSION CUTOUT LENGTH	
2	1.38"	36mm	1.25"	32mm
3	2.06"	52mm	1.94"	50mm
4	2.75"	70mm	2.63"	67mm
5	3.44"	87mm	3.31"	84mm
6	4.13"	105mm	4.00"	102mm
7	4.81"	122mm	4.69"	120mm
8	5.50"	140mm	5.38"	137mm

MINI STRIPANEL (400°F Continuous Ambient)			
No. of Circuits	Mini Panel Part No.	Price \$/Panel	
2	1237-2-*		
3	1237-3-*		
4	1237-4-*		
5	1237-5-*		
6	1237-6-*		
7	1237-7-*		
8	1237-8-*		

MINI STRIPANEL (800°F Continuous Ambient)			
No. of Circuits	Hi-Temp Mini Panel Part No.	Price \$/Panel	
2	1337-2-*		
3	1337-3-*		
4	1337-4-*		
5	1337-5-*		
6	1337-6-*		
7	1337-7-*		
8	1337-8-*		

*Thermocouple Type Code. J, K, T, N, E, R, S, U
2.) Gold plated contacts at extra cost, use suffix "G" (i.e. 1237-2-K-G)

Dynatherm[®]



Heavy Duty Steel Frame is sturdy, will not flex in use.

Universal 19" Rack Frame No. 1241
2-24 circuits supplied in single row
25-48 circuits supplied in double row.


- Universal 19" Racks accept 2 to 48 Circuits of No. 1237 Mini Strippanels. Up to 24 circuits in a single row or up to 48 in a double row may be supplied.
- Circuits can be added in the field without changing frame.
- Thermocouple types can be mixed within panel with each type color coded.
- 19" Rack Frame is made of sturdy 10 ga. steel that will not flex in use. Standard frame is flat black. High-Temp frame is bright silver finish.
- Thermocouple type and circuit numbers are marked on face of Strippanel. Strippanels are numbered starting from "1" unless specified otherwise.
- Strippanels are molded of glass-filled thermoset compounds (will not melt) for high strength and dependability. The color coded panels will withstand ambient temperatures to 400° F (205° C) continuous and 500° F (260° C) intermittent. High-temperature panels (All Hi-Temp panels are color coded red) will withstand ambient temperatures to 800° F (425° C) continuous and 1000° F (540° C) intermittent.
- Inserts are spring loaded to assure positive contact with the negative insert larger to make it virtually impossible to mismatch.
- For corrosive applications, gold plated inserts are available. Caution — system errors can result from use of plated contacts if significant thermal gradients exist at connector.

TO ORDER:

1. Give Code No. 1241 - 48 - K
2. Specify number of circuits ↑
3. Designate Thermocouple Type by Code ↑
4. For Hi-Temp Strippanel: 1341 - 48 - K

CALIB. MARK	INSERT MAT'L. ALLOY		COLOR CODE	HI-TEMP COLOR CODE
	POSITIVE	NEGATIVE		
J	IRON	CONSTANTAN	BLACK	RED
T	COPPER	CONSTANTAN	BLUE	
K	CHROMEL™	ALUMEL™	YELLOW	
N	NICROSIL	NISIL	ORANGE	
R	COPPER	#11 ALLOY	GREEN	
S	COPPER	#11 ALLOY	GREEN	
E	CHROMEL™	CONSTANTAN	VIOLET	
U	COPPER	COPPER	WHITE	
C*	#405 ALLOY	#426 ALLOY	BROWN	

*Gold plated inserts are available at extra cost. Use suffix "G" (i.e. 1241-48-K-G)



MINI RSC PANEL JACK

Mini round single circuit (RSC) module is assembled in a bracket for direct mounting in standard 1/2" electrical box knockout. Self-contained hardware provides front mounting in panels to 1/4" thick. ANSI calibration symbol and color code easily visible from the front. Adaptor available for 3/4" knockout.

DESCRIPTION	CODE NO.	PRICE	
Mini RSC Panel	1231-*		
Adapter Plate for 3/4" knockout	ADP-34		

*with Adapter Plate back side of mounting must be accessible.

When ordering, specify part number, adding ANSI calibration code * as a suffix.

MINI RSC MOUNTING HARDWARE (if ordered separately)			
Mini RSC Hardware	1295		



MINI PANEL IN CONDUIT BOX

Mini Strippanel modules are mounted in conduit box, cast aluminum construction. Circuits are color coded, numbered and lettered with ANSI calibration code. Available with 2 thru 6 circuits. Standard panels are provided with Mini Jacks.

NUMBER OF CIRCUITS	CODE NO.	PRICE	
2	1239-2-*		
3	1239-3-*		
4	1239-4-*		
5	1239-5-*		
6	1239-6-*		

When ordering, specify part number, adding ANSI calibration code * as a suffix.



STANDARD TO MINI ADAPTER

Provides a reliable connection between a standard two pole plug and a mini jack. Available in J or K only.

DESCRIPTION	CODE NO.	PRICE	
STANDARD TO MINI ADAPTER	1044-J 1044-K		